



RTE-DRILLGENT

Product Description:

Aqueous blend of surfactants for water based drilling fluids. Utilized primarily to reduce surface tension and alleviate occurrence of bit balling.

Physical Properties:

Property	Specification
Appearance	Dark brown liquid
Specific Gravity @ 25°C	0.97 -1.02
Pour point (°C)	Below 10 °C
pH (neat)	9 - 11
Solubility	Soluble in water at any temperature

Features and Benefits:

Effectively reduces surface tension at low concentrations and is compatible with a wide range of drilling fluids and additives.

Emulsifies free oils and demonstrates lubricity and reduction in torque.

Maintains performance at high down-hole temperatures (up to 350 F).

Recommended Treatment:

Concentrations in the range of 0.1-05 lb/bbl are recommended to control drilling mud properties. The quantity used would be dependent on the drilling fluid system, amount of oil contamination and type of formation.

Packaging:

Packaged in 208 liter HDPE drums.

Legislation and Handling Recommendations:

Not restricted by any regulatory agency. Refer to the Material Safety Data Sheet (MSDS) for the product prior to usage.

RTE believes in good faith that the information presented in this bulletin is accurate and reliable. No other warranties are given in relation to the information or the products of whatsoever nature, and RTE assumes no responsibility for advice or recommendations made herein or any other information disseminated concerning this product. Under no circumstances shall RTE or its responsible personnel be liable for any special or consequential damages whatsoever.