



## DRILLING FLUID PRODUCTS

### TECHNICAL INFORMATION

#### **SALT-GEL™** ATTAPULGITE CLAY

##### Viscosity Aid for Water based Mud Drilling Fluids

**SALT-GEL** is selectively mined drilling grade attapulgite clay meeting API specifications. **SALT-GEL** is utilized to viscosify water based drilling fluids forming stable gel structure with high yields.

##### Product Specifications:

Property	Specification
<b>Suspension properties as per API 13A Section 7</b>	Exceeds
Viscometer dial reading at 600 rpm	Min. 30
Wet screen analysis on 200 mesh	Max. 8 (wt %)
Moisture Content	Max. 10 %
<b>Bulk Density</b> (kg/m <sup>3</sup> )	850 - 900
<b>Appearance</b>	Beige fine powder

##### Packaging:

Packaged in 22.7 kg (50 lbs) and 25 kg (55 lbs) multiwall paper sacks and in HDPE big bags.

##### Legislation and Handling Recommendations:

Not restricted by any regulatory agency. Refer to the Material Safety Data Sheet (MSDS) for the product prior to use.

© RTE, 2002. ALL RIGHTS RESERVED

RTE believes in good faith that the information presented in this bulletin is accurate and reliable. No other warranties are given in relation to the information or the products of whatsoever nature, and RTE assumes no responsibility for advice or recommendations made herein or any other information disseminated concerning this product. Under no circumstances shall RTE or its responsible personnel be liable for any special or consequential damages whatsoever.